

x5 HD IP ULTRA-LOW LIGHT DOME CAMERA



NEW *CNB-SIRD312IR*

Features

Using Ultra-Low Light sensor

1/2.7" Progressive Scan CMOS(IMX335) 이미지 센서를 사용하면 희미한 빛 환경에서 고화질 및 선명한 색상 이미지를 확인할 수 있습니다.

Powerful zoom capability

5 배 광학 줌, 뛰어난 자동 초점, 2.7 ~ 13.5 mm 초점 범위. 특히, 조리개가 F1.5이기 때문에 다른 어떤 카메라보다도 좋은 화질을 얻을 수 있습니다.

행동분석

지능형 분석을 통해 24x7 모니터링을보다 안정적으로 수행하고 알람 탐지를보다 정확하게 하며 사용자가 정보에 신속하게 응답하고 기록 자료를 신속하게 조사 할 수 있습니다.

Weather Proof Design

IP66 보호기능을 통해 카메라는 비, 눈 또는 폭풍과 상관없이 정상적인 작동을 보장합니다.



Region Entrance



Region Exiting



Area Intrusion



Line Crossing



Unattended Object



Object Missing



Fast Moving

x5 HD IP Ultra-Low Light Dome Camera

NEW CNB-SIRD312IR

Specifications

Camera

Image Device	1/2.7" Progressive Scan CMOS (IMX335)
Effective Pixels	Approx. 5 Mega pixels
Aspect Ratio	HD: 16:9 SD: 4:3
Zoom Ratio	Optical x5
Focal Length	f = 2.7 ~ 13.5mm, Motorized Lens, F1.5
Horizontal angle	(H)29°~108°
MIN. Illumination	COLOR : 0.01 Lux@F1.5 B/W : 0 Lux (IR on)
Day & Night	Auto(CDS/CAM) / Day / Night(ICR)
Focus	Auto/Manual
DNR(2D/3D)	OFF/Level Adjustment(1~5)
Shutter Speed	1 sec ~ 1/10,000sec(60/30 mode) 1 sec ~ 1/10,000sec(50/25 mode)
AGC	Auto/Manual
White Balance	Auto/Indoor/Outdoor/Manual
WDR/BLC	OFF/BLC/WDR(120dB)
Other Function	Defog, HLC, Dynamic slow shutter

General

Sensor In /Out	Built-in 1 Input / 1 Output(Relay)
Audio In / Out	1 Audio In / 1 Audio Out
Video Out	BNC: VBS 1.0 Vp-p
IR distance	More than 35M Wave: 850nm
Power	DC12V / PoE
Approvals*	IK10, KC, IP66
Housing	Weather proof / Vandal Proof Structure
Material	Body : Aluminum Die-casting
Dimension	Net: 141 x 120 mm
Weight	Net: 1.160Kg
Operating Temp.	-30°C ~ 60°C

Network

Ethernet	10Base-T/100Base-Tx
Video Compression	H.264/H.264+/H.265/H.265+
Video Stream	Main 5MP/1080p/720p
	Second D1/CIF/QCIF
	Third 1080p/720p/D1/CIF/QCIF
Stream Type	Video/Complex(Video/Audio) Stream
Frame Rate	20 fps for 1080P/720P/D1/CIF/QCIF 15 fps for 5MP(2952 x 1944)
Bitrate	11Kbps ~ 8Mbps. Supports CBR/VBR
Audio Compression	Two way, G.711 A-law, G.711 μ -law, 128kbps, sampling rate 8kHz
Local Storage	Micro SD/SDHC/SDXC card. Support up to 128GB
IVA	Motion Detection, Occlusion Detection, Line Crossing*, Region entrance/exiting*, Intrusion*, Tampering*, etc
Alarm actions	Email, Micro SD/SDHC/SDXC Record, Relay Output, Snapshot, Notification of Client
Alarm	Pre-Post Alarm
Max No. of Clients	10 users(Depending on user bandwidth)
Web Brower	IE 6.0 above
Protocols Support	IPv4 IPv4/IPv6*, TCP/IP, UDP, RTP, RTSP, RTMP, NTP, HTTP, HTTPS*, SSL*, DNS, DDNS, DHCP, FTP, SMTP, ICMP, SNMP*
	DDNS Public DDNS services Support: www.dyndns.com
	ONVIF Onvif 2.6, Profile S, CGI
	Security User Authentication(ID/PW), IP Address/Mac Address filtering*

Dimension

Unit: mm

